



AC Discrete I/O Modules

Control power for the block is tapped off the input/output device voltages wired to the terminals. No separate block power supply is needed. Configurable features include; Output Pulse Test capability, Selectable Input Filter Time from 10mS to 100mS, Output powerup defaults, Output Hold Last State or default, each circuit has electronic fusing.

	IC660BBD110	IC660BBD101	IC660BBS102	IC660BBS103	IC660BBR100	IC660BBR101
Product Name	Genius Discrete Input Block, 115 VAC Grouped, 16 Point	Genius Discrete I/O Block, 115 VAC Grouped, 8 Point	Genius Discrete I/O Block, 115 VAC/125 VDC Isolated, 8 Point	Genius Discrete I/O Block, 115 VAC/125 VDC Isolated, 8 Point, w/o Failed Switch Diagnostic	Genius Relay Output Block, Grouped, 16 Points, Normally Closed	Genius Relay Output Block, Grouped, 16 Points, Normally Open
Network Support	Genius Bus	Genius Bus	Genius Bus	Genius Bus	Genius Bus	Genius Bus
Input Range	93-132 VAC	93-132 VAC	115 VAC / 125 VDC	115 VAC / 125 VDC	N/A	N/A
Output Range	N/A	93-132 VAC	115 VAC / 125 VDC	115 VAC / 125 VDC	5V to 250 VAC or 5V to 220 VDC; Relay Normally-Closed Relays	5V to 250 VAC or 5V to 220 VDC; Relay Normally-Open Relays
Number of Points	16	8	8	8	16	16
Input and Output Response Time - ON/OFF (msec.)	Input 1 msec plus configurable filter 10 to 100mS in 10mS increments	Input 2msec plus configurable filter 10 to 100mS in 10mS increments; Outputs Zero crossing	Input 2msec plus configurable filter 10 to 100mS in 10mS increments; Outputs Zero crossing	Input 2msec plus configurable filter 10 to 100mS in 10mS increments; Outputs Zero crossing	5.0 msec.	5.0 msec.
Input Impedance	11.6K ohms	13K ohms	13K ohms	13K ohms	N/A	N/A
Load Current Per Point	N/A	2 Amp	2.0 Amp	2.0 Amp	2 Amp	2 Amp
Points Per Common	Two groups of 8	One groups of 8	Four groups of 2	Four groups of 2	Four groups of 4	Four groups of 4
Protection	N/A	Internal electronic short circuit trip. 100ms long time trip	Internal electronic short circuit trip. 100ms (AC), 10ms (DC) long time trip	Internal electronic short circuit trip. 100ms (AC), 10ms (DC) long time trip	N/A	N/A
Diagnostics	Input Diagnostics: Open Wire, Short Circuit	Input Diagnostics: Open Wire, Overtemperature, Failed Switch Output Diagnostics: Short Circuit, Overload, No Load, Failed Switch, Overtemperature, Pulse Test	Input Diagnostics: Open Wire, Overtemperature, Loss of I/O Power, Failed Switch Output Diagnostics: Short Circuit, Overload, No Load, Overtemp., Loss of I/O Power, Failed Switch, Pulse Test	Input Diagnostics: Open Wire, Overtemperature, Loss of I/O Power, Failed Switch Output Diagnostics: Short Circuit, Overload, No Load, Overtemp., Loss of I/O Power, Failed Switch, Pulse Test	None	None
Operating Voltage	93-132 VAC	93-132 VAC	93-132 VAC / 105-132 VDC	93-132 VAC / 105-132 VDC	93-132 VAC / 185-265 VAC	93-132 VAC / 185-265 VAC
Dimensions (H x W x D)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)	8.83" (22.44cm) x 3.50" (8.89cm) x 3.94" (10.00cm)